

# Specifications – AC 22 kW Charging Device

<b>Rated Power</b>	AC : 22 kW
<b>Application Scenario</b>	Residential Type
<b>Input / Output Voltage</b>	Single-phase 400 V (±20%)
<b>Input/Output Current</b>	32 A
<b>Weight</b>	3.8KG
<b>Protection Level</b>	IP55
<b>Frequency</b>	50Hz/60Hz
<b>Connector Type</b>	Type 2
<b>Cable Length</b>	5m
<b>Display</b>	4.3-inch color display, 480 × 272 resolution
<b>Charging Mode</b>	Plug & Charge / Card Authentication
<b>Measurement</b>	Built-in metering (Class B, ±1%)
<b>Installation Method</b>	Wall-mounted or floor-mounted
<b>Protection Functions</b>	Short circuit, surge, earth leakage, overvoltage, overcurrent, undervoltage, over-temperature, emergency stop, rain
<b>Operating Temperature</b>	-30 °C / +50 °C
<b>Dimensions</b>	400mm* 220mm* 142mm
<b>Operating Altitude</b>	<2000m
<b>Relative Humidity</b>	%5~%95
<b>RCD</b>	DC 6mA
<b>EMC</b>	Class B
<b>Certification</b>	CE