

J-OLA

Specifications

Engine

| | |
|---------------------|---|
| Engine Type | OHC, Air-cooled single-cylinder 4 VALVE |
| Engine Displacement | 124.6 cc |
| Max. Power Output | 7.2 kW / 8000 rpm |
| Max. Torque | 10.0 Nm / 6000 rpm |
| Emission Standards | Euro V, EEC |

Chassis, Dimensions and Weight

| | |
|------------------------------|----------------------|
| Length x Width x Height (mm) | 1863 x 708 x 1158 mm |
| Seat Height (mm) | 770 |
| Wheelbase (mm) | 1320 |
| Kerb Weight (kg) | 118 |

Wheels, Suspension and Brakes

| | |
|--------------------|---|
| Front brake | Single disc Φ 220mm / ABS for option |
| Rear brake | Single disc Φ 195mm |
| Tyres (Front/Rear) | Fr: 120/60-13 Rr: 130/60-13 |
| Suspension Front | Telescopic fork Φ 30mm |
| Suspension Rear | single swing |

J-OLA 125CC AC



Max. Power Output (kw/rpm)

10.5

8500r/min

Max. Torque (Nm/rpm)

14

6500r/min

Key Features

- Maximum Speed 90km/h
- Keyless start
- LED lens headlamp
- High-resolution LCD
- 4.6L fuel tank volume
- Disc front and rear brakes
- Front and rear ABS(option)
- 1320mm wheelbase



FUZHOU ALADDIN RONGHAI
TECH CO. LTD.
福州阿拉丁榕海科技有限公司

J-OLA

